

The multi plug 'MAX-L' with collar expands in 4 directions and knots around the screw in hollow building materials (plasterboard, lightweight boards or perforated brick). The collar on the head prevents deep penetration into the drill hole. The plug is made of high-quality polyamide (PA 6) and is suitable for use with wood and chipboard screws.

Temperature resistance: -40°F to +212°F

Safety coefficient: 5



Status: 11.2025

Product specification

Article number	Dimensions Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Box contents	outer carton
10 060	6 x 50	6	60	100 pcs.	4.000 pcs.
10 060	8 x 60	8	70	50 pcs.	2.000 pcs.
10 060	10 x 70	10	80	25 pcs.	1.000 pcs.

Extraction values in kilo-Newton*

Plug/Screw** Ø	aerated concrete block	Perforated brick
6 / 5,0	0,83 kN	1,01 kN
8 / 6,0	1,01 kN	1,39 kN
10 / 7,0	1,60 kN	1,82 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

** The length of the screw must be selected so that it penetrates the dowel completely and protrudes from the tip of the dowel by at least its own diameter.

CONTACT US

+49 (0) 3622 92040
office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

www.huefner-duebel.de
#Hüfner-Dübel GmbH