

The nail plug 'FIX' with cylindrical head made of pure nylon with pre-assembled, galvanised screw nail is suitable for quick installation with high pull-out values in solid building materials. It can be subsequently adjusted using its cross recess. The cylindrical anchor head lies on top like a washer. This is important when fastening thin-walled add-on parts such as signs, sheet metal, metal studs in interior fittings and electrical cable ducts

**Temperature resistance:** -40°F to +176°F

**Safety coefficient:** 5



## Product specification

Article number	Dowels-Dim. Ø x L mm	Nail-Dim. Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation depth min. mm	Effective length max. mm	Box contents	outer carton
11 050	6 x 30	4 x 35	6	35	25	5	200 pcs.	2.000 pcs.
11 050	6 x 35	4 x 37	6	35	25	10	200 pcs.	2.000 pcs.
11 050	6 x 40	4 x 42	6	35	25	15	200 pcs.	2.000 pcs.
11 050	6 x 50	4 x 52	6	35	25	25	200 pcs.	2.000 pcs.
11 050	6 x 60	4 x 62	6	35	25	35	200 pcs.	2.000 pcs.
11 050	6 x 80	4 x 82	6	35	25	55	200 pcs.	2.000 pcs.
11 050	8 x 60	5 x 62	8	45	40	20	100 pcs.	1.000 pcs.
11 050	8 x 80	5 x 82	8	45	40	40	100 pcs.	1.000 pcs.
11 050	8 x 100	5 x 102	8	45	40	60	100 pcs.	1.000 pcs.

## Extraction values in kilo-Newton\*

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

\* All data is based on values determined during factory tests by Hüfner-Dübel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

### CONTACT US

☎ +49 (0) 3622 92040  
✉ office@huefner-duebel.de

### OUR ADDRESS

Gothaer Straße 50  
D-99880 Waltershausen

### ONLINE PRESENCE

🌐 www.huefner-duebel.de  
#Hüfner-Dübel GmbH