

The nail plug "FIX-KRAGEN" made of pure nylon with a cylinder head and galvanised screw nail is suitable for quick fixing in solid building materials. It can be subsequently adjusted using a cross slot. The large collar acts like a washer and simplifies the fastening of objects, even with large holes. It is particularly suitable for perforated angles and perforated sheets.

**Temperature resistance:** -40°F to +176°F

**Safety coefficient:** 5



## Product specification

Article number	Dimension Ø x L mm	Drill bit Ø mm	Drilling depth min. mm	Installation depth min. mm	Effective length max. mm	Box contents	outer carton
11 060	8 x 45	8	45	40	5	100 pcs.	1.000 pcs.

## Extraction values in kilo-Newton\*

Plug Ø	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

\* All data is based on values determined during factory tests by Hüfner-Dübel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

### CONTACT US

☎ +49 (0) 3622 92040  
✉ office@huefner-duebel.de

### OUR ADDRESS

Gothaer Straße 50  
D-99880 Waltershausen

### ONLINE PRESENCE

🌐 www.huefner-duebel.de  
#Hüfner-Dübel GmbH