

The nail plug "FIX-S" made of pure nylon with countersunk head, galvanised screw nail and galvanised washer \varnothing 20 mm is suitable for quick fastening in solid building materials. It can be subsequently adjusted thanks to its cross slot and is recommended for fixing expanded metal, mesh metal and mesh fabric, for example.

Temperature resistance: -40°F to +176°F

Safety coefficient: 5



Product specification

Article number	Dimensions $\varnothing \times L$ mm	Disc \varnothing mm	Drill \varnothing mm	Drilling depth min. mm	Setting depth min. mm	Effective length max. mm	Box contents	outer carton
11 070	6 x 35	20	6	35	25	10	100 pcs.	1.000 pcs.
11 070	6 x 40	20	6	35	25	15	100 pcs.	1.000 pcs.
11 070	6 x 50	20	6	35	25	25	100 pcs.	1.000 pcs.
11 070	6 x 60	20	6	35	25	35	100 pcs.	1.000 pcs.
11 070	6 x 80	20	6	35	25	55	100 pcs.	1.000 pcs.
11 070	8 x 50	20	8	45	40	10	100 pcs.	1.000 pcs.

Extraction values in kilo-Newton*

Plug \varnothing	Concrete C20/25 (B25)	Brick MZ 20	Sand lime brick KSV 20
6	1,5 kN	1,35 kN	1,15 kN
8	2,1 kN	1,95 kN	1,7 kN

* All data is based on values determined during factory tests by Huefner-Duebel GmbH. They serve only as general technical installation information and do not constitute a building authority approval. The possible applications must be checked on site and adapted to the conditions.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
#Hüfner-Dübel GmbH