

The metal cavity plug "MHDS" with pre-assembled screw is suitable for light to medium fixings on chipboard, plasterboard and gypsum fibreboard. Drill the hole as indicated, insert the plug flush and tighten the screw until resistance is felt. The points under the head prevent the plug from turning. Then loosen the screw and fix the component.

The "HRZ" professional cavity plug pliers are recommended for professional processing of \varnothing 4mm, 5mm & 6mm.

Temperature resistance: -40°F to +392°F

Safety coefficient: 5



Product specification

| Article number | Dimensions mm | Drill \varnothing mm | Screws \varnothing mm | Box Contents | Outer carton Contents |
|----------------|---------------|------------------------|-------------------------|--------------|-----------------------|
| 24 101 | 8 x 15 | 14 | M 8 | 100 pcs. | 1.000 pcs. |
| 24 101 | 8 x 21 | 14 | M 8 | 100 pcs. | 1.000 pcs. |
| 24 101 | 8 x 34 | 14 | M 8 | 50 pcs. | 500 pcs. |
| 24 101 | 8 x 50 | 14 | M 8 | 50 pcs. | 500 pcs. |

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
📘 #Hüfner-Dübel GmbH