

The "UMD" universal metal dowel is suitable for quick and easy installation in perforated brick, pumice and aerated concrete. Simply hammer in and the "UMD" is in place. From gas concrete class 6 and for other harder materials such as perforated bricks, pre-drilling as indicated in the table is recommended. The anchor has an internal thread guide for a secure hold of the screw thread. The outer ribbing ensures high pull-out values.

The anchor fulfils the technical regulation for gas pipes in accordance with TRGI 3.3.7.1 in conjunction with an 8 mm hanger bolt. (If the mechanical strength of the pipe connection is not guaranteed with plastic plugs in the event of fire, metal plugs must be used).

Temperature resistance: -40°F to +392°F

Safety coefficient: 5



Product specification

Article Number	Dimensions mm	Drill Ø mm	Drilling depth min. mm	Setting depth min. mm	Box Contents	Outer carton Contents
24 600	5 x 30	5 - 6	35	30	200 pcs.	2.000 pcs.
24 600	6 x 32	7 - 8	40	32	200 pcs.	2.000 pcs.
24 600	8 x 38	9 - 11	50	38	100 pcs.	1.000 pcs.
24 600	8 x 60	9 - 11	70	60	100 pcs.	1.000 pcs.
24 600	10 x 60	12 - 14	70	60	100 pcs.	1.000 pcs.

CONTACT US

☎ +49 (0) 3622 92040
✉ office@huefner-duebel.de

OUR ADDRESS

Gothaer Straße 50
D-99880 Waltershausen

ONLINE PRESENCE

🌐 www.huefner-duebel.de
#Hüfner-Dübel GmbH